

CIN'K - 35OLF

CIN'K - 5000 W TUNGSTEN



- **Type:** Single lens luminaire
- **Source:** 5000 W Tungsten
- **Optics:** 250 mm Fresnel lens

5K Fresnel designed specifically for theatres

Cin'k's 250 mm lens gives an output which exceeds that of comparable 300 mm fixtures, and its theatre-inspired front cassette has no distracting light spill. An ideal tungsten source for theatres and opera houses, large venues and rental houses.

Features

- **Theatre front cassette:** no light spill to distract audiences or performers
- **Accessories holder:** double runners to hold accessories and colour filters
- **Focus reference:** index for easy focus reference
- **Tilt reference on hanging yoke:** index for rapid re-positioning

Optical

- **250 mm lens:** light output equivalent to 'studio' 300 mm fixtures

Construction

- **Made in France :** fully manufactured in Robert Juliat premises retaining complete control over all aspects of quality
- **Air vents:** efficient cooling with no light spill
- **Bodywork:** strong sheet metal construction for durability
- **Moving parts:** smooth at all times, even when hot
- **Captive knobs and handles:** additional security when working at height or in transit
- **Access:** easy access to lamp house and lenses through front opening for fast and efficient maintenance
- **Easy access to all parts:** easy cleaning, re-lamping and maintenance
- **Removable assemblies:** fast-plug cable connectors and complete component assemblies (mirror, condenser set and lamp house assembly) save maintenance and cleaning time
- **Specially designed handle:** for fast cable changing without having to go inside the unit
- **Safety grid:** earthed safety grid fitted as standard
- **Safety first:** front accessories safety cable attachment point

Picture:350LF

DSEN031_350LF - 10/07/2025

Robert Juliat reserves the right to change or alter any of the items detailed on this page, to increase or improve manufacturing techniques without prior notice.

Robert Juliat S.A.S., 32 rue de Beaumont, 60530 Fresnoy-en-Thelle - France
Telephone : +33 (0)3 44 26 51 89 - info@robertjuliat.fr - www.robertjuliat.com

Single lens


ROBERT JULIAT

Source



- **Lamp type:** Tungsten
- **Socket:** G38

| Admissible lamps | Power* | Lumen output* | Colour temperature* | Life* |
|------------------|---------|---------------|---------------------|-------|
| LIF: CP85 (CP29) | 5 000 W | 135 000 lm | 3200K | 400 h |

(*) manufacturer's data

Optics

Characteristics

- **Type:** Single lens
- **Range:** 10° to 54° (Beam angle)
- **Lens:** 250 mm Fresnel lens


Gel filter

- **Shape:** Square
- **Standard size:** 333x333 mm (13.1x13.1 in)


Photometrics

optics: 17°-° / Standard / LIF: CP85 (CP29) 5000W

• Optics @ 17°



Dimensions and weight



Weight: 18 kg (39.6 lbs)


| Height | Length | Width | Yoke | Tilt |
|----------------------|-----------------------|---------------------|----------------------|----------|
| H= 560 mm (22 in) | L= 425 mm (16.7 in) | W= 465 mm (18.3 in) | Y= 270 mm (10.6 in) | TU= TBD° |
| H'= 670 mm (26.4 in) | L1= 250 mm (9.8 in) | W1= TBD mm (0 in) | Y'= 390 mm (15.4 in) | TD= TBD° |
| H1= TBD mm (0 in) | L1'= 290 mm (11.4 in) | | | |
| H2= 450 mm (17.7 in) | L2= 175 mm (6.9 in) | | | |

Shipping

- Weight : 22 kg (48.4 lbs)
- Volume : .14 m³ (4.94 ft³)

Installation

- Minimum distance to illuminated surface: 4.5 m (14.8 ft)
- Operating position:



Construction

- Housing: Steel sheet - Aluminium
- Colour: Black
- Cooling: Convection cooling
- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum case temperature (Tc): 350°C (662°F)
- Total heat dissipation: 17 066 BTU/h
- Ingress Protection (IP) rating: IP20

Electrical compatibility

- 230/240 V - 50 Hz
- 115/120 V - 60 Hz

Warranty

- **Fixture: 2 years**
See General Sales Condition on website

Approvals



Power input



- Type: attached power cord
- Cable: EWKF 3G4
- Length: 3 m (9.8 ft)
- Power connector: 32A blue 2P+E 6h IEC60309 (CEE 32)

Power consumption

| Voltage | Frequency | Current | Power |
|---------|-----------|---------|--------|
| 230 V | 50 Hz | 22 A | 5000 W |

Model

| | |
|--------------|--|
| 350LF | 5000 W Tungsten Single lens luminaire - G38 socket - 250mm Fresnel - 350LF Cin'k |
|--------------|--|

Options

Accessories

| | | |
|--------------------|--|--|
| PF325 | 333x333mm metal filter holder - Weight: 0.52 Kg 1 included | |
| G325L | 333x333mm safety grid - Weight: 0.44 Kg 1 included | |
| CP85 (CP29) | CP85 (CP29) - G38 5000W 230V 400h 3200K lamp | |
| PFR325 | 600x600 mm extended metal filter holder with 4 clips - Weight: 1.11 Kg | |
| CF325 | 4 rotating leaves on a rotating barndoors - 333x333mm (without safety cable) - Weight: 2.11 Kg | |
| PFR CF325 | Extended filter holder and rotating barndoors set - 333x333mm | |
| T/325LF | 325LF lamp compartment - 3 meter power cable with CEE 7/7 (2P +T NF/SCHUKO) connector - Weight: 4.95 Kg | |
| T/326LFV | 326LFV lamp compartment (P.S.U. required) - Weight: 10.48 Kg | |
| T/350LFV | 350LFV lamp compartment - fan cooled front cassette- 3 meter power cable with CEE 7/7 (2P+T NF/SCHUKO) connector | |
| 876 | Hook clamp 40x10mm with 28mm M10 screw for Ø35 to 50mm pipes - SWL: 50Kg - Weight: 1.25 Kg | |
| 880 | Hook clamp 40x10mm with 28mm M10 screw for Ø50 to 63mm pipes - SWL: 50Kg - Weight: 1.36 Kg | |
| CS2 | Safety cable Ø3 mm L= 600mm - SWL: 75 Kg | |